

Item	Working Pressure	2000 psi					
	Description	2-1/16"	2-9/16"	3-1/8"	4-1/8"	6-1/8"	
A	End-to-End, Flanged (Ring Joint)	11-5/8"	13-1/8"	14-1/8"	17-1/8"	22-1/8"	
B	Extreme Width of Body	6-1/8"	7-1/8"	7-3/4"	9-3/4"	12-3/8"	
C	Center of Port to Top of Stem Adapter	13"	33-13/16"	16-13/16"	18-7/16"	22-3/4"	
D	Center of Port to Bottom of Body	5-1/4"	6"	7-1/8"	9-1/8"	12-7/8"	
E	Center of Port to Top of Handwheel Rim	15-3/8"	16-1/8"	19-1/16"	20-11/16"	24"	
F	Handwheel OD	14"	14"	14"	14"	18-1/2"	
	Weight (Flanged)	160 lb	200 lb	240 lb	350 lb	800 lb	
Item	Working Pressure	3000 psi					
	Description	2-1/16"	2-9/16"	3-1/8"	4-1/8"	5-1/8"	6-1/8"
A	End-to-End, Threaded	10-5/8"	12-3/8"	13-5/8"	-	-	-
A	End-to-End, Flanged (Ring Joint)	14-5/8"	16-5/8"	17-1/8"	20-1/8"	24-1/8"	24-1/8"
B	Extreme Width of Body	6-3/4"	7-5/8"	7-1/2"	10-1/2"	21"	12-3/4"
C	Center of Port to Top of Stem Adapter	13"	33-13/16"	16-13/16"	18-7/16"	21-5/16"	22-3/4"
D	Center of Port to Bottom of Body	5-5/8"	6-1/2"	7-3/8"	9-1/8"	11-3/8"	12-7/8"
E	Center of Port to Top of Handwheel Rim	15-3/8"	16-1/8"	19-1/16"	20-11/16"	22-9/16"	24"
F	Handwheel OD	14"	14"	14"	18 1/2"	24"	24"
	Weight (Flanged)	170 lb	220 lb	260 lb	450 lb	750 lb	1000 lb
Item	Working Pressure	5000 psi					
	Description	2-1/16"	2-9/16"	3-1/8"	4-1/8"	5-1/8"	6-1/8"
A	End-to-End, Threaded	10-5/8"	12-3/8"	13-5/8"	-	-	-
A	End-to-End, Flanged (Ring Joint)	14-5/8"	16-5/8"	18-5/8"	21-5/8"	28-5/8"	29"
A	End-to-End, Butt Weld	-	-	-	21 1/2"	-	-
B	Extreme Width of Body	7"	8-3/16"	9-1/4"	10-13/16"	21-3/4"	14-1/8"
C	Center of Port to Top of Stem Adapter	15-1/8"	15-15/16"	16-13/16"	18-7/16"	21-5/16"	22-3/4"
D	Center of Port to Bottom of Body	5-5/8"	6-1/2"	7-3/8"	9-1/8"	11-3/8"	12-7/8"
E	Center of Port to Top of Handwheel Rim	17-3/8"	18-1/8"	19-1/16"	20-11/16"	23-9/16"	24"
F	Handwheel OD	14"	14"	18-1/2"	18-1/2"	24"	24"
	Weight (Flanged)	175 lb	230 lb	360 lb	520 lb	800 lb	1160 lb
Item	Working Pressure	10000 psi					
	Description	1-13/16"	2-1/16"	2-9/16"	3-1/16"	4-1/16"	5-1/8"
A	End-to-End, Flanged (Ring Joint)	18-1/4"	20-1/2"	22-1/4"	24--3/8"	26-3/8"	29"
B	Extreme Width of Body	9-1/16"	9-3/8"	9-13/16"	10-1/4"	12-13/16"	23-1/2"
C	Center of Port to Top of Stem Adapter	15-1/8"	15-1/8"	15-13/16"	16-7/8"	19-11/16"	23-7/8"
D	Center of Port to Bottom of Body	5-3/4"	5-7/8"	6-13/16"	8-1/16"	10-1/16"	13-1/8"
E	Center of Port to Top of Handwheel Rim	17-3/8"	17-3/8"	18-1/8"	18-1/16"	20-15/16"	25-1/4"
F	Handwheel OD	14"	18-1/2"	18-1/2"	24"	24"	24"
	Weight	250 lb	275 lb	370 lb	480 lb	880 lb	1750 lb

Item	Working Pressure	15000 psi			
	Description	1-13/16"	2-1/16"	2-9/16"	3-1/16"
A	End-to-End, Flanged (Ring Joint)	18"	19"	21"	23-9/16"
B	Extreme Width of Body	9-7/8"	9-7/8"	11-1/2"	13-9/16"
C	Center of Port to Top of Stem Adapter	15-1/8"	15-1/8"	17-3/16"	20-15/16"
D	Center of Port to Bottom of Body	5-7/8"	6-1/8"	7-5/16"	9-1/4"
E	Center of Port to Top of Handwheel Rim	17-3/8"	17-3/8"	19-9/16"	22-3/16"
F	Handwheel OD	18-1/2"	18-1/2"	18-1/2"	24"
	Weight	275 lb	300 lb	560 lb	890 lb

