

Descriptions:

The S-Style Ram BOP is available in double forged structures, the single and double ram configurations. The rams are controlled hydraulically with the manual locking. Various rams option are available including the blind ram, various size pipe ram, shear blind ram and the variable bore ram. Structures can be ordered with studded or flanged connections.

S type BOP Dimensions Flanged or Studded

Bore (in)	Working Pressure (psi)	With Shear or Not	Open Volume (L)	Close Volume (L)	Total Weight (lb)	Dimension (in)			Connections	
						L	W	H	Top	Bottom
7-1/16	3000	N	2x1.6	2x2	1759	59.8	21.26	11.02	Studded	Studded
			4x1.6	4x2	3660	59.8	21.26	22.28	Studded	Studded
	5000	N	2x1.6	2x2	1759	59.8	21.26	11.02	Studded	Flanged
			4x1.6	4x2	3660	59.8	21.26	22.28	Studded	Studded
		Y	2x5.8	2x6.2	2348	83.1	21.26	18.7	Flanged	Studded
			4x5.8	4x6.2	4718	83.1	21.26	30.75	Flanged	Studded
	10000	Y	2x8.8	2x9.6		75.9	30.31		Studded	Flanged
			4x8.8	4x9.6	8523	75.9	30.31	46.06	Flanged	Flanged
9	3000	N	2x1.96	2x2.36	1746	68	23.43	11.02	Studded	Studded
			4x1.96	4x2.36	3968	68	23.43	27.95	Studded	Flanged
	5000	N	2x4.4	2x5	3825	80	28.94	24.61	Studded	Flanged
			4x4.4	4x5	8774	80	34.06	32.68	Studded	Studded
		Y	2x9.2	2x10		81.7	34.06	25.59	Studded	Flanged
			4x9.2	4x10	9687	81.7	34.06	40.35	Studded	Flanged
	10000	N	2x5.7	2x6.3	6669	80.6	36.02	36.42	Flanged	Flanged
			4x5.7	4x6.3	12081	80.6	36.02	44.49	Studded	Flanged
11	3000	N	2x5.2	2x6	4057	81.5	26.57	27.17	Flanged	Flanged
			4x5.2	4x6	7848	81.5	34.45	31.5	Studded	Studded
		Y	2x13	2x12.1	4751	96.4	26.57	27.17	Flanged	Flanged
			2x5.2 (Upper)	2x6 (Upper)	8521	96.4	34.45	31.5	Studded	Studded
			2x13 (Lower)	2x12.1 (Lower)						

S type BOP Dimensions Flanged or Studded (Continued)

Bore (in)	Working Pressure (psi)	With Shear or Not	Open Volume (L)	Close Volume (L)	Total Weight (lb)	Dimension (in)			Connections	
						L	W	H	Top	Bottom
11	5000	N	2x5.15	2x5.9	4982	83.1	30.71	25.98	Studded	Flanged
			4x5.15	4x5.9	9381	83.1	34.06	32.68	Studded	Studded
		Y	2x11	2x12	5864	98.8	30.71	25.98	Studded	Flanged
			4x11	4x12	10880	98.8	34.65	51.18	Flanged	Flanged
	10000	Y	2x11	2x12						Flanged
			4x11	4x12	11030	87.87	34.06	41.93	Studded	Flanged
		N	2x6.5	2x7.4	10737	88.58	40.16	40.94	Flanged	Flanged
			4x6.5	4x7.4	17042	88.58	40.16	57.87	Flanged	Flanged
		Y	2x15	2x16.5	8719	96.26	36.22	31.61	Flanged	Flanged
			4x15	4x16.5	16535	96.26	40.16	48.54	Studded	Flanged
13-5/8	2000	N	2x2.28	2x3.55	2998	94.49	28.35	13.19	Studded	Flanged
	3000	N	2x5.85	2x6.65	4453	92.13	29.53	21.85	Studded	Flanged
			4x5.85	4x6.65	7751	92.13	33.23	31.1	Studded	Studded
		Y	2x17.5	2x20	6316	100.9	32.68	23.35	Studded	Flanged
			4x17.5	4x20	12084	100.9	32.68	39.13	Studded	Flanged
	5000	N	2x8.25	2x8.95	7275	94.49	36.22	27.95	Studded	Flanged
			4x8.25	4x8.95	13558	94.49	36.22	53.54	Flanged	Flanged
		Y	2x17.9	2x19.6	7981	106	36.22	27.95	Studded	Flanged
			4x17.9	4x19.6	14154	106	36.22	45.08	Studded	Flanged
	10000	Y	2x14.7	2x16.6	14209	105.1	48.82	37.8	Studded	Flanged
			4x14.7	4x16.6	26345	105.1	48.82	58.46	Studded	Flanged
		Y	2x18.3	2x20.9	14220	110	48.74	38.03	Studded	Flanged
4x18.3			4x20.9	25706	110	48.74	58.7	Studded	Flanged	
16-3/4	5000	Y	2x22	2x25.5	15124	122	46.77	42.32	Flanged	Flanged
4x22			4x25.5	27549	122	46.77	62.4	Flanged	Flanged	
18-3/4		Y	2x26.5	2x31	20768	134.6	52.17	48.9	Flanged	Flanged
			4x26.5	4x31	37523	134.6	52.17	70.75	Flanged	Flanged
20-3/4	3000	N	2x11.65	2x13.65	11828	126.2	46.46	43.31	Flanged	Flanged
			4x11.65	4x13.65	21010	126.2	46.46	50.39	Studded	Flanged
		Y	2x24	2x27	13025	150.3	46.46	27.76	Studded	Flanged
			4x24	4x27	22262	150.3	46.46	45.47	Studded	Flanged
21-1/4	2000	N	2x11.65	2x13.65	10417	126.2	46.46	27.76	Studded	Flanged
			4x11.65	4x13.65	19798	126.2	46.46	45.47	Studded	Flanged
		Y	2x24	2x27	11614	150.3	46.46	27.76	Studded	Flanged
			4x24	4x27	22302	150.3	46.46	45.47	Studded	Flanged
	5000	Y	2x29.7	2x31.1	21451	137.6	54.61	42.17	Studded	Flanged
			4x29.7	4x31.1	38856	137.6	54.61	65.2	Studded	Flanged
	10000	Y	2x28	2x29	39403	152.8	72.64	65.35	Flanged	Flanged
			4x28	4x29	61895	152.8	72.64	87.6	Studded	Flanged
26-3/4	2000	Y	2x33.5	2x35	22465	165.6	63.39	49.61	Flanged	Flanged
			4x33.5	4x35		165.6	63.39			
	3000	Y	2x33.5	2x35	22436	165.6	71.26	38.58	Studded	Flanged
			4x33.5	4x35	42589	165.6	71.26	63.46	Studded	Flanged